

# Container specifications



## 20' standard - steel

Description	Non-metric	Metric
Maximum payload	62,391 lb	28,300 kg
Dimensions	20' x 8' x 8'6"	20' x 8' x 8'6"
Volume	1,165 cubic feet	33 m <sup>3</sup>
Door openings, width	7' 8 1/16"	2,350 mm
Door openings, height	7' 5 1/2"	2,274 mm
Internal, length	19' 4 1/8"	5,896 mm
Internal, width	7' 8 1/2"	2,350 mm
Internal, height to load line	7' 10 3/16"	2,393 mm
Weight, gross	67,197 lb	30,480 kg

Description	Non-metric	Metric
Weight, tare	4,806 lb	2,180 kg



### 40' standard - steel

Description	Non-metric	Metric
Maximum payload	63,640 lb	28,870 kg
Dimensions	40' x 8' x 8'6"	40' x 8' x 8'6"
Volume	2,366 cubic feet	67 m <sup>3</sup>
Door openings, width	7' 8 1/8"	2,340 mm
Door openings, height	7' 5 1/2"	2,274 mm
Internal, length	39' 5 11/16"	12,032 mm
Internal, width	7' 8 1/2"	2,350 mm
Internal, height to load line	7' 10 1/4"	2,393 mm
Weight, gross	71,650 lb	32,500 kg

Description	Non-metric	Metric
Weight, tare	8,010 lb	3,630 kg



### 40' high - steel

Description	Non-metric	Metric
Maximum payload	58,380 lb	28,620 kg
Dimensions	40' x 8' x 9'6"	40' x 8' x 9'6"
Volume	2,684 cubic feet	76 m <sup>3</sup>
Door openings, width	7' 8 1/8"	2,340 mm
Door openings, height	8' 5 3/4"	2,585 mm
Internal, length	39' 5 11/16"	12.032 m
Internal, width	7' 8 1/2"	2,352 m
Internal, height to load line	8' 10 1/4"	2.698 m
Weight, gross	71,650 lb	32,500 kg

Description	Non-metric	Metric
Weight, tare	8,554 lb	3,880 kg



### 45' high - steel

Description	Non-metric	Metric
Maximum payload	60,960 lb	27,650 kg
Dimensions	45' x 8' x 9'6"	45' x 8' x 9'6"
Volume	3,036 cubic feet	85 m <sup>3</sup>
Door openings, width	7' 8 1/8"	2,340 mm
Door openings, height	8' 5 3/4"	2,585 mm
Internal, length	44' 5 11"	13,556 mm
Internal, width	7' 8 1/2"	2,352 mm
Internal, height to load line	8' 10 1/4"	2,698 mm
Weight, gross	71,650 lb	32,500 kg

Description	Non-metric	Metric
Weight, tare	10,690 lb	4,850 kg